

SECTION 1: Identification

1.1. Identification

Product form : Substance
Trade name : HopFlow
Chemical name : Hop, Humulus lupulus, ext.
CAS-No. : 8060-28-4

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Manufacturing of food

1.3. Supplier

Manufacturer/Supplier

Simon H. Steiner, Hopfen, GmbH
Auhofstr. 18
Mainburg, 84048
Germany
T +49 8751 8605 0 - F +49 8751 8605 80

Supplier/Importer

Steiner Hops Ltd.
15A Henley Business park
Pirbright Road
Normandy, Guildford, Surrey, GU3 2DX
United Kingdom
T +44 1992 572 331

Manufacturer

Hops Extract Corporation of America
305 N 2ND Ave Yakima
Yakima, WA, 98902-2690
USA
T +1 509 249 1530

Manufacturer

Hallertauer Hopfenveredelungsges. mbH
Auhofstr. 18
Mainburg, 84048
Germany
T +49 8751 8605 500

Manufacturer/Supplier/Importer

S. S. Steiner, Inc.
1 West Washington Avenue
Yakima, WA 98903
USA
T +1 509 453 4731

Email competent person

sds@kft.de

1.4. Emergency telephone number

Emergency number : Simon H. Steiner, Hopfen, GmbH
Tel.: +49 8751 8605 0 (Montag – Freitag 08:00 – 17:00, Central European Time)

Hallertauer Hopfenveredelungsges. mbH
Tel.: +49 8751 8605 500 (Montag – Freitag 08:00 – 17:00, Central European Time)

Steiner Hops Ltd.
Phone: +44 1992 572 331 (Monday to Friday 8.00-17.00, Greenwich Mean Time)

S. S. Steiner, Inc.
Phone: +1 509 453 4731 (Monday to Friday 8.00-17.00, Pacific Time Zone)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4	H227	Combustible liquid
Skin corrosion/irritation Category 2	H315	Causes skin irritation

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

Serious eye damage/eye irritation Category 2A

H319

Causes serious eye irritation

Skin sensitization, Category 1

H317

May cause an allergic skin reaction

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)

:



Signal word (GHS US)

: Warning

Hazard statements (GHS US)

: H227 - Combustible liquid
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

Precautionary statements (GHS US)

: P210 - Keep away from heat, hot surfaces, sparks, open flames. - No smoking.
P261 - Avoid breathing mist, vapors, spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective clothing, protective gloves, eye protection.
P302+P352 - If on skin: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type

: UVCB

Chemical name

: Hop, Humulus lupulus, ext.

CAS-No.

: 8060-28-4

Name	Product identifier	%	GHS US classification
hop oil (Natural component)	CAS-No.: 8007-04-3	9.6 – 14.4	Flam. Liq. 3, H226 Asp. Tox. 1, H304
3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (Natural component)	CAS-No.: 468-28-0	≤ 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact	: May cause an allergic skin reaction. Irritation.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Flammable liquid and vapor.
Explosion hazard	: Explosive vapor/air mixtures may be formed.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Avoid breathing mist, vapors, spray.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Take up mechanically (sweeping, shoveling) and collect in suitable container for disposal. Notify authorities if product enters sewers or public waters.

Other information : Disposal must be done according to official regulations.

6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapor-air mixture.
Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Avoid contact with skin and eyes. Avoid breathing mist, vapors, spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Keep container tightly closed. Store in a well-ventilated place. Keep cool.
Storage temperature : < 10 °C
Heat-ignition : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep away from heat and direct sunlight.

Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hop, *Humulus lupulus*, ext. (8060-28-4)

No additional information available

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)

No additional information available

hop oil (8007-04-3)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

8.3. Individual protection measures/Personal protective equipment

Hand protection:
In case of repeated or prolonged contact wear gloves. Nitrile rubber. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear
Eye protection:
Wear closed safety glasses. EN 166
Skin and body protection:
Wear suitable protective clothing. EN 13034. EN ISO 13688
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Short term exposure. Filter. A. EN 143

Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous.
Color	: amber
Odor	: No data available
Odor threshold	: No data available
pH	: 3.5 – 4.5
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≈ 81 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Density	: 0.9 – 1 g/cm ³ (68 °F)
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 300 – 500 mPa.s (68°F)
Explosion limits	: No data available
Explosive properties	: Product is not explosive. Explosive vapor/air mixtures may be formed.
Oxidizing properties	: Non oxidizing material.

9.2. Other information

No additional information available

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)

LD50 oral rat	700 mg/kg body weight
---------------	-----------------------

Skin corrosion/irritation : Causes skin irritation.
pH: 3.5 – 4.5

Serious eye damage/irritation : Causes serious eye irritation.
pH: 3.5 – 4.5

Respiratory or skin sensitization : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified

Viscosity, kinematic : No data available

Symptoms/effects after skin contact : May cause an allergic skin reaction. Irritation.

Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

12.2. Persistence and degradability

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	26 % (28 d; (OECD 301D method))

12.3. Bioaccumulative potential

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
Partition coefficient n-octanol/water (Log Pow)	4 – 5.5 (40 °C; pH 7; (OECD 117 method))

12.4. Mobility in soil

3,5-dihydroxy-2,6,6-tris(3-methylbuten-2-yl)-4-(3-methyl-1-oxobutyl)cyclohexa-2,4-dien-1-one (468-28-0)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.7 – 2.9 (Quantitative structure-activity relationship (QSAR))

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Disposal must be done according to official regulations. Do not dispose of with domestic waste. Do not discharge into drains or the environment.
Product/Packaging disposal recommendations	: Recycle or dispose of in compliance with current legislation.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

DOT	IMDG	IATA
14.1. UN number		
Not applicable	Not applicable	Not applicable
14.2. Proper Shipping Name		
Combustible liquid, n.o.s. (Hop, Humulus lupulus, ext.)	Not applicable	Not applicable
14.3. Transport hazard class(es)		
Combustible liquid	Not applicable	Not applicable
14.4. Packing group		
III	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment: No	Not applicable	Not applicable
No supplementary information available		

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

14.6. Special precautions for user

DOT	
UN-No.(DOT)	: NA1993
DOT Special Provisions (49 CFR 172.102)	: 148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

IMDG
No data available

IATA
No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

CAUTION: This product is exempt from all requirements of the Toxic Substances Control Act (exemption for food and food additive according to Toxic Substances Control Act Title 15, Chapter 53, §2602, B (VI))

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

Hop, Humulus lupulus, ext. (8060-28-4)

Regulatory reference
Manufacturing of food

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

SECTION 16: Other information

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

Revision date : 12/07/2022
Data sources : Information provided by the manufacturer. European Chemicals Agency, <http://echa.europa.eu/>.
Department issuing data specification sheet: : KFT Chemieservice GmbH
Im Leuschnerpark 3
D-64347 Griesheim

Phone: +49 6155-8981-400
Fax: +49 6155 8981-500
SDS Service: +49 6155 8981-522

Contact person : Dr. Stefanie Finsterbusch-Kettner
Other information : A safety data sheet is not required for this product. This Product Safety Information Sheet has been created on a voluntary basis.

Full text of H-phrases

H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

HopFlow

Safety Data Sheet

according to US OSHA Hazard Communication Standard (HCS 2012); 29 CFR Part 1910.1200

Abbreviations and acronyms	
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Indication of changes:

Information provided by the manufacturer. Hazards identification. Composition/Information on ingredients. Toxicological information. Regulatory information.

KFT SDS US 00

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.